

**PATENT ABSTRACTS OF JAPAN**

(11)Publication number : 59-066066

(43)Date of publication of application : 14.04.1984

(51)Int.Cl.

H01M 8/02

(21)Application number : 57-174613


(71)Applicant : HITACHI LTD

(22)Date of filing : 06.10.1982

(72)Inventor : SHIMIZU TOSHIO  
DOI RYOTA  
TSUKUI TSUTOMU  
TSUTSUMI YASUYUKI**(54) LIQUID FUEL CELL****(57)Abstract:**

**PURPOSE:** To alleviate the restriction to the attitude of a liquid fuel cell and enable it to be used on a slant by bringing a capillary material into contact with the current-collector-side surface of the anode and immersing one end of the capillary material in liquid fuel.

**CONSTITUTION:** An anode 1 and a cathode 2 which is made by applying an electrode catalyst to one surface of a porous carbon plate before it is sintered, are assembled facing each other with an electrolyte 3 interposed. An oxidant 4 and a cathodic current collector 6 are installed over the surface of the cathode 2 to which the electrode catalyst is not applied. A capillary material 9 is brought into contact with the anodic-current-collector-5-side surface of the anode 1 up to the level sufficient for a liquid fuel 8 to reach the top end of the anode 1. One end of the capillary material 9 is immersed in the fuel 8 contained in a fuel storage chamber 7. A liquid fuel cell constituted in such a manner greatly alleviates the restriction to its attitude and can be used at a considerable slant.

**LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office